

**In the Claims**

Please replace all prior versions of claims in the application with the following list of claims:

Claims 1-29 (Cancelled)

30. (New) A tripod head, in particular a camera tripod head, comprising:
- a base member,
  - a tiltable assembly, which, on the one hand, is connected to said base member so as to be rotatable about a tilt axis and to which, on the other hand, a mounting, particularly a camera mounting, is securely attachable,
  - a means for compensating a tilt moment that occurs during the tilt movement, said means having at least one energy-storing member that is freely supported on said base member,
- wherein
- said means for compensating the tilt moment has a carrier assembly that is attached at a position some distance away from said tilt axis on said tiltable assembly and which acts on said energy-storing member when said mounting tilts and as a result said energy-storing member exerts, via said carrier assembly, an essentially sinusoidal return moment on said tiltable assembly and thus on said mounting, and said carrier assembly has at least one carrier that is movable with said tiltable assembly around said tilt axis and has at least one pulling member that interacts with said carrier and said energy-storing member, with
  - said pulling member, starting from said carrier, running essentially perpendicular to said tilt axis toward a deflection point, and after the deflection, said pulling member running essentially parallel to said tilt axis.
31. (New) A tripod head according to claim 30, wherein said energy-storing member is a pressure spring or a tension spring or a torsion spring or a spiral spring.
32. (New) A tripod head according to claim 30, wherein said pulling member is deflected or turned back at least once during the course between said carrier and energy-storing member.

33. (New) A tripod head according to claim 30, wherein said pulling member is deflected once over the course between said carrier and the one end of at least one pressure spring, and the assignment from said carrier to said tilt axis, the pre-tension of said pressure spring, and the distance  $r_b$  between said tilt axis and the deflection point are chosen such that the counteracting compensating or return moment satisfies the formula

$$M = \left( 1 + \frac{r_{s,\max} - r_b + L_{vw,\min}}{\sqrt{r_b^2 + r_s^2 - 2 \cdot r_b \cdot r_s \cdot \cos \alpha}} \right) \cdot c \cdot r_b \cdot r_s \cdot \sin \alpha$$

with the aim that the value of the fraction between brackets, i.e.  $(r_{s,\max} - r_b + L_{vw,\min})$  is equal to zero or close to zero, or the value between brackets is 1 or as far as possible close to 1, in which formula

$r_{s,\max}$	=	maximum distance between tilt axis and carrier
$r_s$	=	distance between tilt axis and carrier
$r_b$	=	distance between the tilt axis and the pulling member's point of exit from the deflection point
$L_{vw,\min}$	=	minimum spring pre-tension
$c$	=	spring rate of individual pressure spring
$\alpha$	=	respective tilt angle.

34. (New) A tripod head according to claim 30, wherein a set of pressure springs is provided.
35. (New) A tripod head according to claim 31, wherein said at least one pressure spring is a helical spring.
36. (New) A tripod head according to claim 31, wherein said at least one pressure spring is aligned essentially parallel to said tilt axis and can be compressed in this direction.
37. (New) A tripod head according to claim 31, wherein said at least one pressure spring is clamped between a stationary support means and a movable support means, which is movable particularly in the direction of said tilt axis.
38. (New) A tripod head according to claim 30, wherein the one end of said pulling member is connected to said movable support means and the other end is connected to said carrier.

39. (New) A tripod head according to claim 30, wherein said deflection point located between said ends of said pulling member is formed by a deflector roll which is rotatable around its own roll shaft.
40. (New) A tripod head according to claim 39, wherein said deflector roll is mounted so as to be pivotable essentially around an axis that passes through a site where said pulling member, coming from said carrier after deflection, leaves said deflector roll in the direction of said movable support means.
41. (New) A tripod head according to claim 30, wherein said pulling member, starting from said carrier, runs essentially perpendicular to said tilt axis toward said deflection point and, after deflection, runs essentially parallel to said tilt axis to said movable support means.
42. (New) A tripod head according to claim 41, wherein said one end of said pulling member is connected to said movable support means, passes from there, via said deflection point, to said carrier, where said pulling member is connected to said carrier, and from there returns, via said deflection point, back to said movable support means.
43. (New) A tripod head according to claim 42, wherein said pulling member is designed as a continuous cable.
44. (New) A tripod head according to claim 30, wherein at least two pulling members are disposed symmetrically relative to said tilt axis.
45. (New) A tripod head according to claim 30, wherein when there is a symmetrical arrangement on both sides of said tilt axis, a continuous pulling member is provided, said pulling member being of a continuous design in the region of said carriers.
46. (New) A tripod head according to claim 45, wherein a carrier assembly formed from a deflection combination that each comprises two deflection points.
47. (New) A tripod head according to claim 46, wherein said deflection points are formed by a deflector roll, whereby at said two deflection points, one deflection point is formed by a fixed deflector roll and the other deflection point is formed by a pivotable deflector roll.
48. (New) A tripod head according to claim 30, wherein said at least one carrier is rotatable around a shaft that is parallel to said tilt axis.

49. (New) A tripod head according to claim 30, wherein said at least one carrier is perpendicular to said tilt axis, preferably continuous, movable in terms of location and fixable in the respective position.
50. (New) A tripod head according to claim 42, wherein said pulling member passes through or loops around said carrier.
51. (New) A tripod head according to claim 30, wherein said pulling member is clamped within said carrier.
52. (New) A tripod head according to claim 30, wherein said pulling member is inextendible.
53. (New) A tripod head according to claim 52, wherein said pulling member is prestretched.
54. (New) A tripod head according to claim 52, wherein said cable is a wire or a laid or braided steel or aramid-fiber cable.
55. (New) A tripod head according to claim 30, wherein at least one groove is provided within said deflector roll for partly receiving and guiding said pulling member.
56. (New) A tripod head according to claim 30, wherein said carrier is a carrier pin aligned parallel to said tilt axis.